

Claims

1. A convertible (1) with a roof (2), which can be stowed in the rear region (3) of the vehicle beneath a lid part (4), it being possible to open and close the lid part (4), on the one hand, for unblocking an opening (7) for the passage of the roof (2) adjacent to the front region (4a) of the lid part (4) and, on the other, for unblocking an opening (8) for luggage, adjacent to the rear end region (9), an auxiliary frame (11) being disposed beneath the lid part (4) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (14) with the lid part (4) and mounted moveably with respect to the vehicle body in its rear region (12), wherein the multiple joint (14), while the opening (7) for the passage of the roof (2) is unblocked, is held in stood-up position, which enlarges the distance between the lid part (4) and the auxiliary frame (11) relative to that of the closed position.

2. The convertible of claim 1, wherein the multiple joint (14) comprises at least two coupled, partial joints (15; 16), of which one (15) is mounted at the lid part (4) and one (16) at the auxiliary frame (11).

3. The convertible of claim 2, wherein the partial joints (15; 16) are connected with one another over a rigid coupling body (17), which, outside of its connection to the partial joints (15; 16), is freely moveable in the opened position of the lid part (4) for unblocking the opening (7) for the passage of the roof (2).

4. The convertible of one of the claims 1 to 3, wherein the partial joints (15; 16) in each case comprise several guide rods (23, 24; 29, 30), which are pivotably connected with the coupling body (17)

Sub 187
5. The convertible of one of the claims 3 to 4, wherein the partial joints (15; 16) in each case comprise two joint points (21, 22; 25, 26) which are mounted at the coupling body (17).

6. The convertible of one of the claims 3 to 5, wherein the partial joint (15), assigned to the lid part (4), has two joint points (19; 20), which are mounted at the lid part (4), and the partial joint (16), assigned to the auxiliary frame (11), has two joint points (27, 28), which are mounted at the auxiliary frame (11).

7. The convertible of one of the claims 1 to 6, wherein the partial joint (16), which is connected with the auxiliary frame (11), causes the guide rod (23; 24) of the partial joint (15), which is connected with the lid part (4), to stand up over a movement of the auxiliary arm (11) and a coupling with the coupling body (17).

8. A convertible (101) with a roof (102), which can be stowed in the rear region (103) of the vehicle beneath a lid part (104), it being possible to open and close the lid part (104), one the one hand, for unblocking an opening (107) for the passage of the roof (102), adjacent to the front end region (115) of the lid part (104) and, on the

other, for unblocking an opening (108) for luggage, adjacent to the rear end region (109) of the lid part (104), an auxiliary frame (111; 111.1) being disposed beneath the lid part (104) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (114; 114.1) with the lid part (104) and mounted moveably with respect to the vehicle body in its rear region (112; 112.1), wherein the multiple joint (114; 114.1), during the unblocking of the opening (107) for the passage of the roof (102), is held in an opened position, which increases the distance between the lid part (104) and the auxiliary frame (111; 111.1) in comparison to the distance in the closed position.

9. The convertible of claim 8, wherein the multiple joint (114; 114.1) is a quadruple joint, two joint points (116, 117; 116.1, 117.1) being assigned to the lid part (104) and two further joint points (118, 119; 118.1, 119.1) being assigned to the auxiliary frame (111; 111.1).

10. The convertible ~~vehicle~~ of one of the claims 8 and 9, wherein the joint point or points (118, 119, 118.1, 119.1), assigned to the auxiliary frame (111, 111.1), are held so that they can be shifted with respect to the auxiliary frame (111, 111.1).

11. The convertible ~~vehicle~~ of claim 10, wherein the shiftability during the opening of the lid part (104) for unblocking the opening (108) for luggage is inhibited.

Sub
A9-12

12. The convertible vehicle of one of the claims 8 to 11, wherein at least one elongated hole, functioning as a sliding block guide (123; 124; 123.1) is constructed for shifting the joint point or points (118, 119, 118.1, 119.1) assigned to the auxiliary frame (111, 111.1).

13. The convertible of one of the claims 8 to 12, wherein two joint points (118, 119) in the auxiliary frame (111) are held in two elongated holes (123; 124), which extend essentially linearly and, in the closed position, in the driving direction.

convertible
⑭. The device of claim 13 wherein, in the closed position of the lid part (104), the joint points (118, 119) are held in elongated holes (123; 124) in an extreme front position and, during the opening process of the lid part (104), for unblocking the opening (107) for the passage of the roof, initially can be shifted in a rearward direction and, as the opening process is continued, can be shifted once again in the direction of the extreme front region.

Sub
A10-19

19. The device of one of the claims 8 to 12, wherein the joint (114.1) is a quadruple joint and two of the joint points (118.1; 119.1) are assigned to the lid part (104) and two further ones to the auxiliary frame (111.1), the joint points (118.1; 119.1), assigned to the auxiliary frame (111.1), being moveable in a common sliding-block guide (123.1).

Sub
All 7

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	